

WASHLET®

COMPARISON CHART

		G500	S350e	S300e	C200	C100
		MS970CEMFG (elongated)	SW583 (round) SW584 (elongated)	SW573 (round) SW574 (elongated)	SW2043 (round) SW2044 (elongated)	SW2033 (round) SW2034 (elongated)
CLEANSE	COLOR: Cotton (#01), Sedona Beige (#12)	#01 / #12	#01 / #12	#01 / #12	#01 / #12	#01 / #12
	REAR CLEANSE	•	•	•	•	•
	SOFT REAR CLEANSE	•	•	•	•	•
	FRONT CLEANSE	•	•	•	•	•
	WIDE FRONT CLEANSE		•	•		
	OSCILLATING CLEANSE	•	•	•	•	•
	PULSATING CLEANSE	•	•	•	•	
	INSTANTANEOUS WATER HEATING		•	•		
	WATER PRESSURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS
	WATER TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	3 SETTINGS
WAND POSITION ADJUSTMENT	•	•	•	•	•	
AIR	AIR PURIFIER (DEODORIZER)	•	•	•	•	•
	AIR DRYER	•	•	•	•	•
	AIR TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	3 SETTINGS
SEAT	HEATED SEAT	•	•	•	•	•
	HEATED SEAT TEMPERATURE CONTROL	5 SETTINGS	5 SETTINGS	5 SETTINGS	5 SETTINGS	3 SETTINGS
	SOFT CLOSE SEAT AND LID	•	•	•	•	•
SENSOR	SEAT SENSOR	•	•	•	•	•
	AUTOMATIC OPEN AND CLOSE LID	•	•			
	AUTOMATIC FLUSH	•				
	NIGHT LIGHT		•			
REMOTE CONTROL	REMOTE CONTROL	•	•	•	•	SIDE PANEL
	REMOTE CONTROLLED SEAT	•	•			
	REMOTE CONTROLLED FLUSH	•				
HYGIENE	REMOVABLE LID	•	•	•	•	•
	<i>e</i> water+™		•	•		
	PREMIST™		•	•	•	•
	WAND CLEANING MODE	•	•	•	•	•
	SELF-CLEANING WAND	•	•	•	•	•
ENERGY SAVING	ENERGY-SAVE TIMER	3, 6, 9 HOURS	3, 6, 9 HOURS	3, 6, 9 HOURS		
	AUTO ENERGY SAVER	•	•	•	•	•
	ON / OFF BUTTON	•	•	•		

POWER RATING		120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz	120V AC, 60Hz
RATED POWER USAGE		406W	835W	835W	406W	406W
LENGTH OF POWER CORD		Maximum length 3.6 ft.	Maximum length 4 ft.	Maximum length 4 ft.	Maximum length 3.94 ft.	Maximum length 3.94 ft.
WASHLET	NOZZLE FLOW RATE	REAR	9.8 - 20.3 oz. / min.	9.1 - 14.5 oz. / min.	9.1 - 14.5 oz. / min.	9.1 - 14.5 oz. / min.
		SOFT	9.8 - 18.6 oz. / min.	10.8 - 14.5 oz. / min.	10.8 - 14.5 oz. / min.	9.1 - 14.5 oz. / min.
	FRONT	9.1 - 18.6 oz. / min.	9.8 - 14.5 oz. / min.	9.8 - 14.5 oz. / min.	9.8 - 14.5 oz. / min.	9.8 - 14.5 oz. / min.
		WATER TEMPERATURE	86°F - 104°F	86°F - 104°F	86°F - 104°F	95°F - 104°F
DRYER	AIR TEMPERATURE	104°F - 130°F	95°F - 140°F	95°F - 140°F	86°F - 140°F	86°F - 140°F
	CAPACITY OF AIR	9.54 ft3 / min.	10.24 ft3 / min.	10.24 ft3 / min.	9.54 ft3 / min.	9.54 ft3 / min.
HEATED SEAT	SURFACE TEMPERATURE	82° F - 97° F	82° F - 97° F	82° F - 97° F	82° F - 95° F	82° F - 97° F
WATER SUPPLY PRESSURE		7 psi - 109 psi	7 psi - 109 psi	7 psi - 109 psi	7 psi - 109 psi	7 psi - 109 psi
WATER SUPPLY TEMPERATURE		33°F to 95°F	33°F to 95°F	33°F to 95°F	33°F to 95°F	33°F to 95°F
AMBIENT TEMPERATURE		33°F to 104°F	33°F to 104°F	33°F to 104°F	33°F to 104°F	33°F to 104°F
SIZE	ROUND	-	15-5/16"W x 18-7/8"D x 3-15/16"H	15-5/16"W x 18-7/8"D x 3-15/16"H	15-3/8"W x 18-7/8"D x 7-3/8"H	18-13/16"W x 18-7/8"D x 7-3/8"H
	ELONGATED	15-15/16"W x 28-9/16"D x 25-1/8"H	15-5/16"W x 20-3/4"D x 3-15/16"H	15-5/16"W x 20-3/4"D x 3-15/16"H	15-3/8"W x 20-7/8"D x 7-3/8"H	18-13/16"W x 20-7/8"D x 7-3/8"H